UMASIPALA WASOLUNDI

" The City of Heritage "

ULUNDI MUNICIPALITY

QUOTE NO: 18/2023/2024

REQUEST FOR FORMAL WRITTEN QUOTATIONS

Bids are hereby invited from suppliers registered on the Ulundi Municipality supplier database for the **Supply and delivery of Asphalt Hotmix** as per the attached specification.

The quotation must be submitted on the letterhead of your enterprise in a clearly indicating the quote number addressed to reach us by not later than **12 February 2026 at 12h00 midday.**

Only service providers registered in Bid no. **18/2023/2024 PANEL OF SERVICE PROVIDERS FOR SUPPLY AND DELIVERY OF ASPHALT PRODUCTS FOR A PERIOD OF YEARS (2024/2025 TO 2026/2027) FINANCIAL YEARS)**will be considered.

Tel: 087 287 0018 Email: zmakhoba@ulundi.gov.za

NB: ONLY EMAILED AND HAND DELIVERED QUOTATIONS WILL BE ACCEPTED

Supply Chain Management Unit, Ulundi Municipality, Cnr. Princess Magogo Str. And King Zwelithini Str.

The following conditions will apply:

- Prices quoted must be valid for at least thirty (30) days from the date of your offer.
- Prices quoted must be firm and must be inclusive of VAT.
- A firm delivery period must be indicated.
- Filled MBD forms 4, 6.1, 8, and 9.
- The service provider must be registered and compliant on Central Supplier Database (CSD)
- NB: No quotations will be considered from persons in the service of the state.
- Failure to comply with these conditions may invalidate your offer.
- The Ulundi Municipality reserves the right to accept the quote in whole or in part.
- All service providers must provide their copy of Identity document and CSD report
- 80/20 preference point system will be used and evaluated as follows:

Price – 80
Black – 5
Women – 5
Youth – 5
Disability – 5

Specification

Description	Quantity
Hot Asphalt • Factory-produced hot-mixed asphalt comprising clean, durable graded aggregate, suitable bituminous binder and mineral filler. • The material shall be suitable for municipal road maintenance, pothole repairs and pavement patching, with a nominal aggregate size of 9.5 mm or 13.2 mm. • The mix shall be uniform, durable, resistant to rutting and deformation, and suitable for proper placement and compaction under normal road-maintenance conditions. • Material shall comply with applicable SANS, COLTO and/or relevant South African road construction requirements and be supplied with relevant product/mix design information upon request. The supplier shall ensure that: • Hotmix asphalt is delivered at a temperature suitable for placement and compaction. • Loads are protected from contamination and excessive heat loss.	289 tons

Enquiries: P.M.S Buthelezi

: 087 287 0026

Approved

BY _____

SCM MANAGER

05/02/2026